Oblong Master Links with Sub-Assemblies typically link at the top of the sling and slip over the crane hook. The large links support and distribute the weight of any load. This Grade 100 Sub-Assembly With Large Sub-Links is fabricated from premium fine grain alloy steel and finished with high a quality heat treatment.



### **FEATURES**

- Grade 100
- Made from premium fine grain alloy steel
- Quenched and tempered before proof testing
- 4:1 Safety Factor for Chain Slings
- Blue powder coat finish
- Meets or exceeds OSHA, Government, NACM, and ASTM specs



WWW.KITO.CA | 1.888.322.KITO (5486)

All specifications, dimensions and drawings are available at www.kito.ca, or call our Customer Service staff for friendly and expert advice on models and options.

V10 ALLOY CHAIN ACCESSORIES

### **GRADE**

• 100

#### **FINISH**

• Blue Powder Coat Finish

### **STANDARDS**

 Meets or exceeds OSHA, Government, NACM, and ASTM specs

## **ATTACHMENT**

Sub-Assemblies

#### HEAT TREATMENT

Quenched and tempered before proof testing

### **ORIGIN**

Made in Italy

## **LINK TYPE**

• Master Link with Large Sub-links

## **APPLICATION**


· Overhead Lifting

### **MATERIAL**

• Premium Fine Grain Alloy Steel



## **DIAGRAM DRAWINGS**





3

## PRODUCTS SPECIFICATIONS

Product	Manufacturer Part No.	Trade Size (Inches)	Trade Size mm	Dim D	Dim L	Dim P	Dim D1	Dim L1	Dim P1	Lbs. Per Ea.	Working Load Limit for Triple & Quad Leg @ 60°
8852100	XUSAK2014	3/4	19	0.748	2.953	5.315	0.591	2.756	4.724	4.3	11200
8852200	XUSAK2316	7/8	22	0.906	3.543	6.299	0.669	3.150	5.512	6.9	14800
8852300	XUSAK2720	1	26	1.063	3.937	7.087	0.787	3.740	6.299	10.9	22900
8852400	XUSAK3327	1-1/4	32	1.299	4.331	7.874	1.063	4.331	7.480	21	39000
8852500	XUSAK4033	1-1/2	38	1.496	5.906	10.827	1.299	5.118	9.055	37.5	58700
8852600	XUSAK4540	2	50	1.969	9.843	13.780	1.496	5.906	10.827	71.9	91700
8852700	XUSAK5045	2-1/4	56	2.205	9.843	13.780	1.772	7.087	13.386	106.1	110900

4

KITO