

PEERLESS® STANDARD PLATE HOOKS

Peerless® Standard Plate Hooks are designed for the most popular chain sizes - 9/32", 3/8", 1/2", 5/8" and 7/8". They are proof tested to the same values as the corresponding chain - therefore, the same Working Load Limit applies. Fabricated from alloy steel, Plate Hooks can be furnished on Registered Slings as well as with various chain assemblies. Accoloy Plate Hooks are intended for use in handling plates, flats, and structurals.



PEERLESS® STANDARD PLATE HOOKS

STANDARDS

- Certified to OSHA and ASME standards

ORIGIN

- Made in USA

APPLICATION

- Custom Lifting intended for use in handling plates, flats and structurals

MATERIAL

- Alloy Steel

PEERLESS® STANDARD PLATE HOOKS

PRODUCTS SPECIFICATIONS

Product	Chain Size Inches	Chain Size mm	Dim A (in.)	Dim B (in.)	Dim C (in.)	Dim D (in.)	Dim L (in.)	Dim M (in.)	Dim N (in.)	Dim R (in.)	Dim T (in.)	Dim W (in.)	Lbs. Per Ea.	Working Load Limit (Lbs.)
PHA028	9/32	7	2.000	1.750	2.500	0.930	1.000	3.680	0.120	0.310	0.630	2.500	2.80	4200
PHA038	3/8	10	2.625	3.000	4.310	1.180	1.120	6.380	0.180	0.380	0.750	2.750	5.70	7400
PHA050	1/2	13	3.500	4.000	4.380	1.500	1.500	7.370	0.250	0.500	1.000	3.500	13.0	13000
PHA063	5/8	16	4.375	5.000	5.430	1.870	1.880	9.250	0.310	0.630	1.250	5.000	26.50	20400
PHA075	3/4	20	5.188	6.000	6.500	2.380	2.250	10.880	0.380	0.750	1.500	5.750	42.00	30000
PHA088	7/8	22	6.000	7.000	7.630	2.500	2.630	13.680	0.430	1.000	1.750	6.000	65.00	40000